



# HYDRAULIC POWER PACK

MODEL: 22kW

Standard 22kw HPU suited to operate large range of tooling and various other applications. Operator friendly unit with basic control and function. Built in low level and overheat protection.

- Sacrificial weld plates supplied on unit
- Primary structure in accordance with DNV 2.7-1
- Can be supplied with auxiliary pressure and flow control valves to suit client requirement
- Pressure, return and drain line filtration

## WHAT'S IN THE BOX

- INDUSTRY STANDARD 3/4 WING TYPE HYDRAULIC CONNECTOR FOR PRESSURE AND RETURN
- ISO B CONNECTION FOR CASE DRAIN
- CROWFOOT CONNECTION FOR BOWMAN COOLER
- SUPPLIED WITH 20M ELECTRICAL CABLE
- OPERATING MANUAL

## TECHNICAL SPECIFICATIONS

Max Flow	75 l/min @ 60Hz operation
Max Pressure	320 bar @ 35 l/min 60 Hz operation
Motor	22kW WEG 4 pole 3ph 380/440v 50/60Hz
Starter	Star Delta in SS enclosure
Filtration	MP Filtri pressure, return & drain
Cooler	Bowman seawater heat exchanger
Reservoir	200 litre, low oil & high temp trips
Frame	4 point lift in accordance with DNV 2.7 1
Dimensions	1492 x 800 x 1615 mm
Weight	1,000 kg
Certification	Full certification package for MPI, slings, shackles & load test

SOS-TDS-175