



# HYDRAULIC REEL

MODEL: HR300

Standard tooling downline. 200m twin line supplied. Max pull of 1000kg. Flow range 15-60 lpm. Working pressure 200 bar. In addition to supporting tooling fleet can be utilised for various other operations.

## WHAT'S IN THE BOX

- INDUSTRY STANDARD 3/4 WING TYPE HYDRAULIC CONNECTOR ON DOWN LINE
- 6MTR DECK WHIPS SUPPLIED WITH UNIT (PRESSURE, RETURN AND DRAIN)
- OPERATING MANUAL

- Sacrificial weld plates supplied on unit
- Primary structure in accordance with DNV 2.7-1
- Can be supplied with additional drain line on request
- Pay in/out local control
- Tool hot/cold local control
- Fitted with rotary coupling

## TECHNICAL SPECIFICATIONS

Capacity	300 m Twin Hose Umbilical
Max Pull	1000 kg
Flow	15 – 60 l/min
Pressure	200 bar
Connection	6 m hoses c/w Q.D. Couplings
Weight	1500 kg Tare, 3000 kg Gross
Certification	Full certification package for hose test, MPI, slings, shackles & load test
<b>DRUM DIMENSIONS</b>	
Core	800 mm
Flange	350 mm
Width	800 mm
<b>DIMENSIONS</b>	
Length	1770 mm
Width	1770 mm

SOS-TDS-178