



## LARGE HYDRAULIC HAGGLUND REEL

Primarily used for handling hose, umbilicals and cables for many applications. Drum can be split/divided for installation of various bundles.

- Local control for pay in/out
- Sacrificial weld plates supplied on unit
- 3500KG payload
- 304mm dia access to drum core
- Rotary union or slings of various sizes can be installed

### WHAT'S IN THE BOX

- OPERATING MANUAL
- CERTIFICATION
- 6M DECK HOSES  
(PRESSURE, RETURN, DRAIN)

### TECHNICAL SPECIFICATIONS

Drum Dimensions	Core 1067 mm Dia. / Flange 2275 mm Dia. / Drum Width 1650 mm
Hydraulics	Max Pressure 210 bar, Flow up to 80 l/min (7rpm)
Max Line Pull	5000 kg
Motor/Brake	Hagglund, 11084cc/rev, HD62 - 111000 - A0 - R0 - 00 - 00
Control	Walvoil SD 18/2 Motor Spool spring centred. Relief valve set to 110 bar (3te)
Rotary Union	Optional - Slew ring bearing 340 mm ID
Couplings	Supply & Return 1" Parker 61 Series, Drain ½" ISO7241B
Frame	Welded steel Channel skid, Box section top lifting frame - Pad eyes x 4
Dimensions	3100 x 2450 x 2700 mm H
Weight	6500 kg Tare, 10,000kg Gross
Certification	Full certification package for hose test, MPI, slings, shackles & load test

SOS-TDS-