



SL55



SL80

SOFTLINE CUTTERS

MODELS: SL55, SL80

Although heavy duty the SL55 and SL80 are compact and lightweight. Pressure supply of 210 bar and 690 bar max respectively. Ideally suited to cut softlines, polypropylene and fibre ropes.

MODEL SL55

- Can be ROV configured via mounting holes on cutter
- Side open entry allows for easy placement
- Cutting capacity of up to 54mm

MODELS SL80

- Can be ROV configured via mounting holes on cutter
- Side open entry allows for easy placement
- Cutting capacity of up to 80mm

WHAT'S IN THE BOX

- INDUSTRY STANDARD 3/4 WING TYPE HYDRAULIC CONNECTOR
- 1.5MTR TOOL WHIPS SUPPLIED WITH UNIT
- OPERATING MANUAL

TECHNICAL SPECIFICATIONS

| | SL55 | SL80 |
|----------|-----------|-----------|
| Capacity | 54 mm Dia | 80 mm Dia |
| Pressure | 210 bar | 690 bar |
| Weight | 4.52 kg | 14.2 kg |
| Length | 410 mm | 647 mm |
| Width | 150 mm | 188 mm |
| Depth | 44 mm | 138 mm |
| Porting | 1/4" BSP | 1/4" BSP |